

PRODUCT DATA SHEET

V030926

PneumatiX

PM10300VSD

MODEL	PM10300VSD
AIR DELIVERY	1000 LPM @ 8 BAR 35 CFM
MAX PRESSURE	145 PSI 10 BAR
MOTOR POWER	7.5KW 10HP
VOLTAGE	3PH / 415V D-Curve 20A Double GPO Dryer
WARRANTY	1 YEAR

The PneumatiX PM10300VSD rotary screw air compressor is a compact solution for workshops with a compressed air requirement under 1.0 m³/min or 1000 L/Min (35 CFM). Featuring a space saving tank mounted air dryer and inline air filters you can be sure that your air tools and machinery are receiving treated air with minimal contamination. The PM10300VSD is powered by a permanent magnetic motor, working in conjunction with an advanced digital inverter system that varies the motor and compressor speed according to compressed air demand, potentially delivering energy savings up to 35%.

- ✓ Fully featured space saving plug and play solution
- ✓ 145 PSI | 10 Bar max pressure
- ✓ AS1210 2010 air receiver design
- ✓ Worksafe registered
- ✓ Programmable compressor start/stop calendar

- ✓ Installed pre filter and post filter
- ✓ Variable speed energy saving PM motor
- ✓ Tank mounted air dryer
- ✓ Digital controller
- ✓ Inovance VSD



SPECIFICATIONS

RPM	1440-3600 RPM	OUTLET DIA	¾"
NOISE	65 dB (A)	IP RATING	IP23
AIR RECEIVER	300 LTR AS1210-2010 Hazard Level C Worksafe Reg WSV-0150569915	DRIVE METHOD	DIRECT DRIVE INTEGRATED PM Synchronous IE4
AIR DRYER	PMD1200 Refrigerated 1200LPM 2-10°C	INLINE FILTERS	1.0 & 0.01 MICRON PM10PREINLINE/POSTINLINE
WEIGHT	312kg	DIMENSIONS (LxWxH)	1760x640x1460mm
SHIPPING WEIGHT	330kg	SHIPPING DIMENSIONS (LxWxH)	1780x660x1480mm

SERVICE PARTS

PM10-2500HR-FK	2500HR KIT AIR/OIL/AIR&OIL SEP FILTERS
PM10-7500HR-SVK	7500HR KIT SUCTION VALVE
PM10-12500HR-OGK	12500HR KIT OIL GAUGE AND O RING
PM10-20000HR-SK	20000HR KIT BEARINGS SHAFT SEALS
PM10PARTPREELEM	INLINE FILTER PRE ELEMENT 1.0 MIC
PM10PARTPOSTELEM	INLINE FILTER POST ELEMENT 0.01 MIC

FOR INSTALLATION AND SERVICE CONTACT 1800 342 224

