

PRODUCT DATA SHEET

V030926



- 100% DUTY CYCLE
- VARIABLE SPEED – ENERGY SAVING UP TO 35%
- LOW NOISE – 70dB

MODEL	PM30VSD
AIR DELIVERY	3200 LPM @ 8 BAR 113 CFM
MAX PRESSURE	145 PSI 10 BAR
MOTOR POWER	22KW 30HP
VOLTAGE	3PH / 415V D-Curve 50A Circuit Breaker
WARRANTY	1 YEAR



The PneumatiX PM30VSD rotary screw air compressor is a compact base mount solution for workshops with a compressed air requirement under 3.2 m³/min or 3200 L/Min (113 CFM). The PM30VSD is powered by a permanent magnetic motor, working in conjunction with an advanced digital inverter system that varies the motor and compressor speed according to compressed air demand, potentially delivering energy savings up to 35%.

- ✓ Variable speed energy saving PM motor
- ✓ 145 PSI | 10 Bar max pressure
- ✓ AS1210 2010 air/oil separator design
- ✓ Worksafe registered air oil separator
- ✓ Digital controller
- ✓ Programmable start/stop calendar
- ✓ Inovance VSD

SPECIFICATIONS

RPM	1400-3500 RPM	OUTLET DIA	1"
NOISE	70 dB (A)	IP RATING	IP23
AIR OIL SEPARATOR	17 LTR AS1210-2010 Hazard Level D Worksafe Reg WSV-0151461936	DRIVE METHOD	DIRECT DRIVE INTEGRATED PM Synchronous IE4
WEIGHT	250kg	DIMENSIONS (LxWxH)	920x900x1145mm
SHIPPING WEIGHT	260kg	SHIPPING DIMENSIONS (LxWxH)	970x950x1255mm

SERVICE PARTS

PM30-2500HR-FK	2500HR KIT AIR/OIL/AIR&OIL SEP FILTERS
PM30-7500HR-SVK	7500HR KIT SUCTION VALVE
PM30-12500HR-OGK	12500HR KIT OIL GAUGE AND O RING
PM30-20000HR-SK	20000HR KIT BEARINGS SHAFT SEALS

FOR INSTALLATION AND SERVICE CONTACT 1800 342 224

